

PHANTOM®

CURRENT SENSOR





PHANTOM, the best wireless condition monitoring system worldwide. With the **current sensor** you can measure up to 4 different phases between 50A and 500A.

The signal from the **PHANTOM** sensors is encrypted which ensures the reliability of the information and the security of your data.

MEASUREMENT

Product code	EPH-C31
Input	4 clamps (<i>split core current transformer</i>)
Frequency Range	50-60 Hz
Status	Minimum / Maximum / Average / Amp Hour
Data receiving interval	Min: 1 min - Máx: 120 min
Clamps	50 / 100 / 250 / 500 Amp

POWER SUPPLY

Battery lifetime	12,000 measurements
Main power supply	3.5 VDC / 1.5 A (<i>2xAA batteries</i>) 5-24 VDC / 1A (<i>external power supply</i>)

CONNECTIVITY AND SOFTWARE

Wireless protocol	Bluetooth BLE 5.0
Operating frequency	2.4 GHz
Transmission power	±8 dBm
Signal strenght range	-90 dBm to -30 dBm
Power output range	-4 dBm to +8 dBm (<i>configurable</i>)
Devices compatibility	iOS and Android devices (<i>WISER VIBE & PHANTOM™ Manager</i>) and PHANTOM™ Gateway
Software compatibility	DigivibeMX 11 M30 & PHANTOM™ Version / PHANTOM™ Manager and WiSER VIBE
Operating distance	100 m Line sight*
Contains FCC ID	X8WBT840

DIMENSIONS AND FIXTURE

Dimensions (<i>h x w</i>)	125 mm x 100 mm x 37 mm
Protection grade	IP67
Weight	500 grams
Housing material	ABS, stainless steel

ENVIRONMENTAL CONDITIONS

Operating temperature	-40 °C to 80 °C (<i>40 °F to 176 °F</i>)
-----------------------	--